









LL ARENA BARNDOOR 1kW/2kW

are special designed shielding barndoor that allow smooth shading dependent on required blanking ratio. LL ARENA Barndoors allows mechanical lamps dimming, which removed the need for lamp restart.

Main applications

- Sport floodlights
- Special floodlights,...

Architectural





LL ARENA BARNDOOR 1kW/2kW

Dimensions in mm: LL ARENA BARNDOOR


1kW:


2kW:





LL ARENA DRIVER











LL ARENA DRIVER

Power connection

Data connection



LL ARENA BARNDOOR

Technical specification:

LL ARENA BARNDOOR	
Control data connection:	2m cable with 5pin connectors
Power connection:	Only by LL ARENA DRIVER
Net weight:	1kW: 5,7kg / 2kW: 6,7kg
Dimensions LxWxH:	1kW: 800mm x 530mm x 61mm (close) 2kW: 900mm x 630mm x 61mm (close)
IP:	IP20, IP43 option
Ambient temp. (Ta):	0° C ~ +40°C for IP 20 -20°C ~ +40°C for IP43 version
Cooling:	Active cooling by low noise fan
Materials and finish:	Steel / Aluminium combination

LL ARENA DRIVER	
Power connection:	100-260V AC, 50-60Hz
Power output:	2 pcs for DC 24V motor drive
Data connection:	DMX512 by XLR In/Out for IP20 DMX512 by Cable In/Out for IP65
Net weight:	0,5kg
Dimensions LxWxH:	260mm x 153mm x 77mm
Ambient temp.(Ta):	0° C ~ +40°C for IP 20 -20°C ~ +40°C for IP65 version
Installation:	Surface mounting



Motion details

Order data:

IP20, IP43

0,0	
Order code	Product name
LL41 700	LL ARENA BARNDOOR 1kW
LL41 750	LL ARENA BARNDOOR 2kW
LL41 800	LL ARENA DRIVER 230V, IP20/IP65 (on request)
LL41 830	LL ARENA DRIVER 24V, IP20/IP65 (on request)
LL41 850	ADAPTER for fixing of barndoor on luminaire

LEADER LIGHT s.r.o.
M. Gorkeho 33
05201 Spisska Nova Ves
SLOVAK REPUBLIC
Tel.: +421 (0)2 44457511
Tel.: +421 (0)2 44457514
Fax: +421 (0)2 44457525
sales@leaderlight.sk

www.leaderlight.eu